



Lockable bicycle rack



000 071 128D

ŠKODA OCTAVIA (5E)
 ŠKODA FABIA (NJ)
 ŠKODA SUPERB (3V)
 ŠKODA KODIAQ (NS)
 ŠKODA CITIGO (NF)
 ŠKODA RAPID (NH3)
 ŠKODA KAROQ (NU)

Material: High-strength steel + plastic

More secure transportation | Premium-quality workmanship | Tests

The **bicycle rack** in the ŠKODA Original Accessories range provides a **secure means of transporting bicycles**, for example when embarking on a cycling holiday over the summer. This accessory is not only guaranteed **not to damage** your vehicle, but it is also completely safe to use: Fitting the rack does not impact how the car handles, meaning that any warranty claims to which you are entitled will remain unaffected. The bicycle rack's unique **design, high-quality workmanship and proven construction** make it easy to mount your bicycle on the roof of your vehicle, secure it in place, and take it down again later. The rack **can be locked** to provide your bicycle with better protection against attempted theft. It can be fitted either to the oval roof bars using the T-groove on the roof rack or to the rectangular roof bars. Securing the bicycle frame to the rack is easy and a firm hold is achieved using a folding lever. Hard-wearing, premium-quality plastic straps are provided for securing the rims to the tyres. The bicycle rack **has passed the relevant load tests and safety tests**. The maximum roof load permitted on the vehicle (including the basic rack, bicycle rack and bicycle(s) being transported) can be found in the registration document for your vehicle. For safety reasons, the maximum permitted roof load must not be exceeded.

Associated products:

Lockable ski and snowboard box / 5L6 071 175 / 175A / 175B
 Lockable ski or snowboard rack with aluminium profile / 000 071 129H

Installation time: 20 TU

Set contents:

Bicycle rack, key (x 2), bracket for the T-groove (x 3), bracket for the oval roof bars (x 3) (use of the brackets depends on the type of rack), fitting instructions.

Diameter:

Tube diameter 22 - 70 mm or oval 65 x 80 mm.

Load capacity:

Max. load capacity 17 kg.

Installation position:

On the basic roof rack or transverse roof rack using the T-groove, or on the rectangular roof bars.

Maintenance:

Standard solution of soapy water or conventional cleaning agents suitable for use on plastics. Do not use abrasive cleaning agents or chemical solvents.

Guarantee:

24 months.
 Does not apply to signs of normal wear and tear.

Weight: 3,5 kg

Transport